

TDS TECHNICAL DATA SHEET

JUPITER
Recess Down light



Description:

Indoor recessed mounting Circular Down light with aluminium anodized bright finish rear reflector and centrally frosted glass cover suitable for horizontally mounted single/twin 26 W CFL Lamp.



Technical Specification:

Frame: Pretreated CRCA MS with epoxy powder coated finish.

Reflector : Aluminium anodized faceted bright finish back reflector and frosted glass cover

Mounting Clips : 3 nos. spring steel retaining clips for positioning in false ceiling.

Gear Tray : Pre-treated CRCA MS with epoxy powder coated finish.



Internal Wiring: PVC insulated single strand copper conductor.

Mains Terminal: 10 amps. suitable for terminating 2.5 sq.mm. conductor.

Hardware: MS, Zinc plated & passivated.

Earthing: 1 No. inside, suitable for 2.5 sq. mm conductor.

Ballast: Option available for both Electro Magnetic Ballast (EMB) & Electronic Ballast (EB).



Cut Out Dia. 210 mm.

Nominal Dimensions in mm, Tolerance +/- 2 mm

Range:

CAT.REF:	Lamp	Voltage	Ballast	Capacitor	Mains current	Power factor	Approx Wt.(Kg)
SDLHR126 CF CFG	1x 26 CFL	240V	EMB	NA	0.32 A	>0.50	1.28
SDLHR 126 CF CFG EB1 /P3	1x 26 CFL	240V	EB	NA	0.12 A	>0.90	1.02
SDLHR 226 CF CFG	2x 26 CFL	240V	EMB	NA	0.64 A	>0.50	1.75
SDLHR 226 CF CFG EB1 /P3	2x 26 CFL	240V	EB	NA	0.23 A	>0.90	1.13

Installation:

- Suitable for cut out Dia. 210 mm in ceiling.
- Three nos. spring steel clips provided for mounting in ceiling.

Application:

Offices, Hotels, Software parks, Hospitals, Conference rooms etc.



DRAWN	PB-SM	DRG.NO :	TD 03-005
CHECKED	SN	REV. NO:	0
APPROVED	SC	DATE:	19.01.2009
Luminaire Business Group			
Surya Roshni Ltd, Padma Tower-I, Rajendra Place, New Delhi-110008			

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in detail from the data given here.