

TDS TECHNICAL DATA SHEET

MERCURY
Recess Down light



Description:

Indoor recessed mounting aluminium pressure die-cast Circular aimable non-integral Down light with aluminium anodized matt finish reflector suitable for single 35W CDMT lamp(G-12 lamp holder).



Technical Specification:

Housing : Die-cast aluminium with epoxy powder coated finish.

Reflector : Aluminium anodized matt finish back reflector with front glass cover.

Mounting Clips : 2 nos. spring steel retaining clips for positioning in false ceiling.


Internal Wiring: Silicon insulated multi strand copper conductor.

Mains Terminal: 10 amps. suitable for terminating 2.5 sq.mm. conductor.

Hardware: MS, Zinc plated & passivated.

Earthing: 1 No. inside, suitable for 2.5 sq. mm. conductor earthing.

Ballast: Needs to be used in conjunction with an appropriate electromagnetic control pack and to be mounted separately.



Cut Out Dia.188 mm.

Nominal Dimensions in mm, Tolerance +/- 2 mm

Range:

CAT.REF:	Lamp	Voltage	Ballast	Capacitor	Mains current	Power factor	Approx Wt (Kg)
SDLAR 135 CDMT	1X35 CDMT	240V	ECP	NA	0.170 A	NA	0.90

Installation:

1. Suitable for cut out Dia. 188 mm in ceiling.
2. Two nos. spring steel clips provided for mounting in ceiling.

Application:

Offices, Hotels, Software parks, Hospitals, Conference rooms etc.

Note: Use suitable control pack(SCP 35 MH)



DRAWN	PB-SM	DRG.NO :	TD 03-007
CHECKED	SN	REV. NO:	1
APPROVED	SC	DATE:	27.03.2009
Luminaire Business Group			
Surya Roshni Ltd, Padma Tower-I, Rajendra Place, New Delhi-110008			

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in detail from the data given here.